

2.1 Specification



Model no.	PREMTA000
Dimension (WxHxD)	120mm x 120mm x 16mm
Max. number of unit	16(Group Control)
Applicable unit type	Air conditioner, ERV, DX ERV
Display	5 inch color, Full touch screen
Power	12V DC
Surrounding Conditions	Operating Temperature : 0~40 °C Storage Temperature : -20~60 °C Humidity : 0~90%

Features

Standard Features

- | | |
|---|----|
| Maximum Number of indoor Units (per controller) | 16 |
| Maximum Number of Controllers (per group) | 2 |
- Room temperature display
 - Operation – On/Off
 - Mode Auto/Cool/Dry/Heat/Fan Only(For AC)
 - Ventilation Mode (for ventilator)
 - Occupied cooling and heating setpoints
 - Fan Speed – Auto/Low/MED/High/Power
 - Discharge vanes – Auto/Swing/Fixed
 - Controller lock function
 - Static pressure setting
 - Function setting for plasma filter, electric heat , humidifier elevation grille , ventilation kit , and auxiliary heat option
 - Error code display during unit or system malfunction
 - Power failure compensation (48hours)

Advanced Function

- 2 set-point Auto change over
- Energy Monitoring & Management
- Scheduling : Weekly, Monthly, Yearly